

412TW-PA-15264



CURRENT HYPERSONIC AND SPACE VEHICLE FLIGHT TEST AND INSTRUMENTATION

John J. Spravka^{*} and Timothy R. Jorris[†]

**AIR FORCE TEST CENTER
EDWARDS AFB, CA**

DATE June 22, 2015

**DISTRIBUTION A. Approved for public release ; distribution is unlimited.
412TW-PA-15264**

**AIR FORCE TEST CENTER
EDWARDS AIR FORCE BASE, CALIFORNIA
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

**4
1
2
T
W**

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 22-06-2015		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To) 22 – 26 July 2015	
4. TITLE AND SUBTITLE Current Hypersonic and Space Vehicle Flight Test and Instrumentation				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) John J. Spravka* and Timothy R. Jorris†				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AND ADDRESS(ES) 412 OG/Hypersonic CTF John J. Spravka Lt Col Timothy R. Jorris 195 E. Popson Ave Edwards AFB, CA 93524				8. PERFORMING ORGANIZATION REPORT NUMBER 412TW-PA-15264	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) N/A	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT DISTRIBUTION A. Approved for public release A: distribution is unlimited.					
13. SUPPLEMENTARY NOTES CA: Air Force Test Center Edwards AFB CA CC: 012100					
14. ABSTRACT Hypersonic flight test applies to suborbital, space transit, and space access vehicles. Recent programs are being initiated by the US Air Force, Defense Advanced Research Programs Agency (DARPA), NASA, and commercial companies. The USAF and DARPA are pursuing technologies to meet the objectives of the High Speed Strike Weapon program. DARPA is also looking for new ways to satisfy the goal of Operationally Responsive Space; a means of inserting a payload into orbit in hours instead of months at a cost of millions instead of hundreds of millions. One of the primary challenges to testing these systems will be collecting the data generated by these high speed vehicles. Recent news of foreign involvement in the pursuit of hypersonic technologies should make the importance of hypersonic advancements very evident. This paper is aimed at addressing the current flight test demand. A historic look will be used to showcase lessons learned from previous programs. These lessons will be juxtaposed with current and future programs with the intent of avoiding their replication. Lastly, a new flight test instrumentation system for atmospheric sensing is introduced. It has the potential to replace Rawindsonde balloons and pacer aircraft as a truth source for test-day atmospheric conditions. Its range of operation can accommodate hypersonic flight test, but its utility can be leveraged by a wide range of flight test programs.					
15. SUBJECT TERMS Hypersonic, flight test, instrumentation, space access, space transit, operationally responsive space, scramjet, boost glide, test & evaluation					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 44	19a. NAME OF RESPONSIBLE PERSON 412 TENG/EN (Tech Pubs)
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code) 661-277-8615

Current Hypersonic and Space Vehicle Flight Test and Instrumentation

John J. Spravka^{*} and Timothy R. Jorris[†]

Hypersonic Combined Test Force, Edwards AFB, CA

Abstract

Hypersonic flight test applies to suborbital, space transit, and space access vehicles. Recent programs are being initiated by the US Air Force, Defense Advanced Research Programs Agency (DARPA), NASA, and commercial companies. The USAF and DARPA are pursuing technologies to meet the objectives of the High Speed Strike Weapon program. DARPA is also looking for new ways to satisfy the goal of Operationally Responsive Space; a means of inserting a payload into orbit in hours instead of months at a cost of millions instead of hundreds of millions. One of the primary challenges to testing these systems will be collecting the data generated by these high speed vehicles.

Recent news of foreign involvement in the pursuit of hypersonic technologies should make the importance of hypersonic advancements very evident. This paper is aimed at addressing the current flight test demand. A historic look will be used to showcase lessons learned from previous programs. These lessons will be juxtaposed with current and future programs with the intent of avoiding their replication. Lastly, a new flight test instrumentation system for atmospheric sensing is introduced. It has the potential to replace Rawindsonde balloons and pacer aircraft as a truth source for test-day atmospheric conditions. Its range of operation can accommodate hypersonic flight test, but its utility can be leveraged by a wide range of flight test programs.

^{*} Deputy, Hypersonic Combined Test Force (CTF), Edwards AFB, CA; john.spravka@us.af.mil

[†] Lt Col, USAF, Ph.D. Director, Hypersonic CTF, Senior Member SFTE, timothy.jorris@us.af.mil

I. Introduction

The advancement of hypersonic technologies is designed to support the Conventional Prompt Global Strike [1] and the High-Speed Strike Weapon (HSSW) [6] programs being managed by the Air Force Research Lab (AFRL) and Defense Advanced Research Projects Agency (DARPA) [7]. While these advancements present challenges in vehicle design in aerodynamics, flight controls, structural loads, heating and propulsion, they also present a challenge to collecting the data generated by these high speed vehicles during flight.

The premise of this paper is to reacquaint the academic and flight test community with past data collection technologies and introduce them to future potential methods for collecting data on high speed, unmanned test vehicles. Past projects' data collection systems and future potential data collection systems are reviewed.

II. Previous Program Data Collection Systems

Conventional or legacy air vehicle data collections systems are well known and in use on numerous test aircraft programs such as F-35, F-22, B-2, and C-17. Sub- and Supersonic air vehicle instrumentation systems are typically able to transmit/receiver data at establish MBS with a constrained bandwidth. Transmission/reception max range limits are typically on the order of hundreds to thousands of miles which can be extended through telemetry relay antennas. Past test programs that pushed the boundaries of air vehicle data collection technologies include AFRL X-51 Scramjet Engine Demonstrator and DARPA Hypersonic Technology Vehicle (HTV-2). TM data transmission/reception for these programs was very difficult and costly due to 1) the high speed at which the vehicles were traveling and 2) the extended ranges over which the vehicles flew over water.

A. X-51A Scramjet Engine Demonstrator

The X-51A was launched from a B-52 over the Point Mugu Sea Range. TM data were transmitted/received over an air vehicle powered and glide flight range of approximately 350 nm from the point of release from the B-52. The X-51A program utilized three different TM instrumentation platforms to collect data from the X-51A. Data was collected on the B-52 launch platform (Figure 1 below) both prior to and after X-51A release. Data were also collected by a ground stations at Vandenberg AFB and on San Nicholas Island within the Pt Mugu Sea Range. Data were also collected by a specially instrumented Navy P-3 aircraft stationed approximately 260 nm from the initial launch location at an altitude of approximately 20,000 ft. The transmit/receive range of the P-3 instrumentation suite was approximately 200 nm.




Figure 1 X-51A mounted under wing of B-52 at Edwards AFB





Figure 2 X-51A Launch profile over restricted water range

Valuable data were collected and relayed on all four powered flights by these TM assets. Flight one on 26 May 2010, had 200 seconds of scramjet burn accelerating to Mach 5 [10]. For the second flight on 13 June 2011, the scramjet lit successfully but failed to transition to full power [11]. For the third flight on 14 Aug 2012, the X-51A safely separated from the B-52 and the rocket booster fired as planned. However after 16 seconds, a fault was identified with one of the cruiser control fins. Once the X-51A separated from the rocket booster, approximately 15 seconds later, the cruiser was not able to maintain control due to the faulty control fin and was lost [12]. The fourth and final flight was a record-setting 210 seconds of scramjet combustion reaching a hypersonic speed of 5.1 Mach number [8]. On powered flight #4 the X-51A transmitted TM continuously from its release location from the B-52 to its eventual splash-down point in the Pacific Ocean.

B. Boost Glide Vehicles

A boost glide vehicle, for this paper, refers to an unpowered hypersonic vehicle that is launched from a ground based booster and then glides after separation. The Air Force flew the Hypersonic Technology Vehicle 2 (HTV-2) and the Army flew the Advanced Hypersonic Weapon (AHW). The two programs have similar challenges except their mission distances are significantly different. HTV-2 was launched from Vandenberg AFB with a planned flight to Kwajalein Atoll [13] approximately 3000 nm away, whereas AHW only flew from Kauai in Hawaii to Kwajalein Atoll [14], as seen in Figure 2.




Figure 2 HTV-2 and AHW Launch Locations

i. Hypersonic Technology Vehicle 2 (HTV-2)

The depiction in Figure 3 shows the entire HTV-2 flight profile [15]. The vehicle was launched atop a Minotaur IV Lite from Vandenberg AFB, CA [16]. The first flight on 22 Apr 2010 collected 9 minutes of unique flight data but didn't complete its full mission. "The Engineering Review Board (ERB) concluded that the anomaly resulted from flight control authority limitations to operate at the angle of attack the vehicle was programmed to fly for the speed and altitude of the flight. Detailed analysis conducted by the ERB revealed that the most probable cause of the HTV-2 flight anomaly was higher-than-predicted yaw, which coupled into roll thus exceeding the available control capability at the time of the anomaly". [17]




Figure 3 DARPA Falcon HTV-2 Flight Profile

The second flight on 11 August 2011 successfully demonstrated stable aerodynamically-controlled flight at speeds up to Mach 20 for nearly three minutes; however this flight also ended prematurely. “The ERB concluded that the ‘most probable cause of the HTV-2 Flight 2 premature flight termination was unexpected aeroshell degradation, creating multiple upsets of increasing severity that ultimately activated the Flight Safety System.’” [18]

The data collected for each of these flights was instrumental in being able to determine the causes of each vehicle failure during flight and will be extremely valuable in guiding the design of future hypersonic flight vehicles. Collecting the data to support each of these flights was again, a challenge due to both the speed of the vehicle and the distance traveled during its flight. In order to continuously collect that TM data throughout the vehicles flight trajectory it was necessary to assemble a “string of pearls” instrumentation assets over the course of the planned trajectory. This string of pearls consisted of land, sea and air based instrumentation platforms.

Specifically, the land assets, like the X-51A resources, consisted of Vandenberg and Pt Mugu Sea Range ground stations. The sea assets consisted of specially instrumented ships deployed to sea for a period of several days to weeks to allow for travel time to the pre-planned location and to accommodate any flight delays. The air instrumentation assets again included specially equipped P-3 aircraft. As one would expect, the cost of operating all of these assets for the period of time required was in the millions of dollars for just one flight.

ii. Army’s Advanced Hypersonic Weapon (AHW)

The flight of the AHW lasted less than 30 minutes on 17 November 2011. “The AHW is a first-of-its-kind glide vehicle, designed to fly within the earth's atmosphere at hypersonic speed and long range, was launched from the Pacific Missile Range Facility, Kauai, Hawaii, to the

Reagan Test Site, U.S. Army Kwajalein Atoll, Marshall Islands.” [14] Figure 2 shows the relationship between Vandenberg AFB, Kauai, and Kwajalein.

III. Future Data Collection Systems

A. DARPA Airborne Launch Assist Space Access (ALASA)

The goal of a project funded by DARPA called the Airborne Launch Assist Space Access (ALASA) program, started in late 2011, is to develop an air launch system that can place a 45-kilogram (100-pound) payload into orbit for less than \$1 million per mission [21]. Achieving that cost goal led DARPA to focus on what the real cost drivers of launch operations are. “If I’m going to hit a million-dollar-per-flight target, I’ve got to do things in such a fundamentally different way that I change the cost equation for all the stuff in a space launch that has nothing to do with the rocket,” said Mitchell Burnside Clapp, the DARPA ALASA program manager [21]. The Boeing ALASA concept intends to use F-15 aircraft that require no modifications. The rocket, for example, will use the same communications protocols as weapons systems typically mounted on that aircraft. “ALSA is not a weapon, but it does talk the same language as weapons speak,” Clapp said. “There are no software changes needed for the F-15. That is a huge advantage.” [21]



Since the ALASA payload will be deployed in low earth orbit (LEO) the payload launch platform instrumentation system will require a range equal to its eventual payload deployment altitude and cross range from the instrumentation relay and endpoint reception systems on the ground.

B. AFRL/DARPA Reusable Booster System Program

The Reusable Booster System (RBS) Pathfinder was “a promising approach to meet the Air Force’s future spacelift needs. The RBS consists of an autonomous, reusable, rocket-powered first stage with an expendable upper stage stack. The reusable first stage launches vertically and carries the expendable stack to the staging point. From the staging point, the reusable first stage returns directly to the launch base, landing aircraft-style on a runway.” [2] Figure 4 shows a graphic of the boost back concept.




Figure 4 Reusable Booster System (RBS) Conceptual Profile

A potential test flight profile of the reusable first stage is shown below in Figure 9. TM data collection and relay assets will have to not only be capable of transmitting/receiving data over a long range horizontally but also vertically. This presents new challenges because air assets used on previous programs such as the P-3 has a service ceiling altitude of only 23,000 ft.




Figure 5 Reusable Boost System Example Trajectory

C. Experimental Spaceplane (XS-1)

The Experimental Spaceplane (XS-1) [5], solicited by DARPA, is aimed at developing a reusable first stage to deploy a 3K – 5k lb payload to orbit for under \$5M per launch. Take-off and landing can be horizontal, vertical or a combination of both. An artist concept is shown in Figure 6. Again, the instrumentation transmit/receive assets would have to be capable to transceiving data over a very long range at low to high altitudes.




Figure 6 Artist Concept of Experimental Spaceplane (XS-1)

D. High Speed Strike Weapon System

AFRL and DARPA have teamed up to manage two different hypersonic propulsion technology development programs; Tactical Boost Glide (TBG) and Hypersonic Air-breathing Weapon Concept (HAWC). Both programs are designed to develop necessary technologies to achieve hypersonic or near-hypersonic speed in a cruise missile sized platform. AFRL is in the early stages of developing the required technologies to support these end products.

i. Tactical Boost Glide (TBG)

Boost glide vehicles achieve their high speed by being boosted by a high thrust rocket to high altitude and gliding back down to a lower altitude. TBG will have an intended range that is “tactical” and less than HTV-2. The Army’s Advanced Hypersonic Weapon (AHW) is a boost glide vehicle and flew 3,700 km on its first test flight [32]. Both HTV-2 and the AHW required a long line of aerial and ship-based TM collection and relay platforms to transmit the data back to the control room. This type of TM support is very expensive. Despite the TBG reduced flight range, testing in this flight regime will still require range assets that are able to support delivering TM data across long ranges and at high altitudes. Many present day and future programs are not funded to a level that would support repeating the “string of pearls” TM collection and relay system that supported HTV-2. In order to avoid this high cost new TM collection and relay systems have to be developed to provide the same level of performance at a much cheaper cost.

ii. Hypersonic Air-breathing Weapon Concept (HAWC)

Due to the long distance of the anticipated HAWC test flight profiles HAWC testing will also require range assets that are able to deliver TM data across long ranges while avoiding the cost of traditional “string of pearls” TM data collection and relay systems.

IV. Proposed TM Data Collection/Relay Technology Systems

A. Aircraft Platforms

A number of UAVs have already served as sensor data and TM relay platforms supporting a specific program or purpose. However, they have typically been single individual systems not a group of systems working together supporting one flight vehicle or program. In order to adequately support a hypersonic or space transit flight test program these UAVs would have to be able to stay aloft for potentially days at a time to support launch delays. There would have to be sufficient numbers of them to support the long distances traveled by hypersonic test vehicles. The instrumentation systems onboard those UAVs would have to have sufficient power to reach boost glide test vehicles at very high altitudes.

Another area of potential use for UAV TM platforms is air vehicle imaging. Obtaining infrared or electro-optical images of a hypersonic or space transit vehicle during flight can greatly enhance anomaly investigation and resolution. Vehicle heating can be observed and used to determine structure materials deterioration or failures during flight. The imagery can also be compared with existing models and updated so as to influence future designs. Atmospheric sensing is another capability that when paired with a UAV platform can


Potential UAV platforms that could support the above-described functions are Global Hawk, Predator, Lockheed Martin's Integrated Sensor in Structure Blimp. One program supportability issue would include the cost of sustaining these systems when not actually supporting test execution. These costs would include the proficiency training required of the UAV operators and maintaining and upgrading the UAV and ground station hardware and software.

B. Space-based Platforms

There are already in place several satellite based options to collecting and relaying TM data. One is the NASA Tracking and Data Relay System (TDRS). The initial setup cost can range anywhere from \$250K - \$1M [33]. However, once the operation configuration is set the system can support data collection/relay at a cost of only \$130 per minute. Other potential satellite networks that could possibly support the hypersonic and space transit flight test TM requirements are InmarSat [34], Iridium [35], Orbcomm [36], ViaSat [37] and Tactical Targeting Network Technology [38]. So while TDRS and similar networks of satellites are continually being updated with faster and larger bandwidth capability, existing and future capability must be assessed to determine if they will meet future hypersonic and space transit vehicle test requirements.

V. Additional Flight Test Instrumentation

The Office of the Secretary of Defense (OSD) High Speed Systems Test (HSST) program is developing atmospheric sensing technology that could replace weather balloons and chase aircraft; particularly since a hypersonic chase aircraft is currently not available. The High Altitude LIDAR Atmospheric Sensing (HALAS) system is a ground based, portable LIDAR system using an ultra-violet laser and scanner system to measure atmospheric conditions (density, temperature, pressure, wind speed/direction, O₂ content) along a vehicle's flight path at altitudes up to 80 km (250k feet). This will result in significantly more accurate flight test data and vehicle performance estimates with low uncertainties and better spatial and temporal resolution. The system also has the capability to provide near real-time and highly accurate measurements at lower altitudes to support range safety operations.



Based on predicted performance, the HALAS uncertainty is significantly better than traditional Rawinsonde balloon data. This comparison only considers the atmosphere in the near vicinity of the balloon, it does not take into account uncertainty improvements gained by multiple balloons or modelling. However, such balloon corrections traditionally do not result in an order of magnitude improvement, as demonstrated with the HALAS.

Altitude (kft)	Balloon Uncertainty	HALAS Uncertainty
20	0.47%	0.023%
30	0.49%	0.021%
40	0.63%	0.022%
50	0.71%	0.027%
60	1.01%	0.036%
70	1.30%	0.050%
80	1.87%	0.069%
90	2.86%	0.092%
100	4.57%	0.120%

VI. Conclusions

There are multiple hypersonic and space transit vehicle technology programs working to satisfy the Department of Defense and NASA objectives. Each is assaulting the challenges inherent in the hypersonic arena. One of these challenges is the collection and relay of vehicle TM data for real time and post flight data analysis. Recent programs, such as the X-51A and HTV-2 achieved these objectives at a high cost which cannot be overcome by future test programs. It is the role of the flight test community to explore and identify those TM data collection/relay technologies that can deliver the required performance to support numerous different types of test vehicles at a reasonable cost.

References

- [1] A. F. Woolf, "Conventional Prompt Global Strike and Long-Range Ballistic Missiles: Background and Issues," 6 July 2012. [Online]. Available: <http://fpc.state.gov/documents/organization/167962.pdf>.
- [2] Air Force Materiel Command, "Reusable Booster System (RBS) Pathfinder," Reusable Booster System (RBS) Pathfinder, 05 Apr 2010. [Online]. Available: https://www.fbo.gov/index?s=opportunity&mode=form&id=6ef1c3c8f3ef6732bf86e3eae914f5c6&tab=core&_cview=1.
- [3] Inside AF.mil, "X-37B Orbital Test Vehicle," 3 March 2011. [Online]. Available: <http://www.af.mil/information/factsheets/factsheet.asp?id=16639>.
- [4] C. Thomas, "NASA's Commercial Crew Program Progressing for Future of U.S. Human Spaceflight," 3 August 2012. [Online]. Available: <http://www.nasa.gov/exploration/commercial/crew/ccicap-announcement.html>.
- [5] DARPA, "Experimental Spaceplane Shooting for "Aircraft-Like" Operations in Orbit," 17 September 2013. [Online]. Available: <http://www.darpa.mil/NewsEvents/Releases/2013/09/17.aspx>.
- [6] AFRL-Eglin Research Site, "High Speed Strike Weapon (HSSW) Demonstration Program Industry Day," 30 May 2012. [Online]. Available: https://www.fbo.gov/index?s=opportunity&mode=form&id=129942a86380453c656ded23b1a6a9e7&tab=core&_cview=0.
- [7] DARPA, "Hypersonics-The New Stealth," 6 July 2012. [Online]. Available: <http://www.darpa.mil/NewsEvents/Releases/2012/07/06.aspx>.
- [8] D. Mayer, "X-51A Waverider Achieves History in Final flight," 88th Air Base Wing Public Affairs, 3 May 2013. [Online]. Available: <http://www.wpafb.af.mil/news/story.asp?id=123346970>.
- [9] B. L. Reed, "Flight Test Challenges & Risks for the X-51A Scramjet Engine Demonstration Program," in *SETP Dayton Symposium*, Wright-Patterson AFB, OH, 2012.

- [10] Wright-Patterson Air Force Base , "X-51 Waverider makes historic hypersonic flight," 26 May 2010. [Online]. Available: <http://www.wpafb.af.mil/news/story.asp?id=123206524>.
- [11] Air Force Materiel Command, "Second hypersonic flight ends prematurely, brings new flight test data," 15 Jun 2011. [Online]. Available: (<http://www.afmc.af.mil/news/story.asp?id=123260080>).
- [12] Inside AF.mil, "X-51A flight ends prematurely," 15 August 2012. [Online]. Available: <http://www.afmc.af.mil/news/story.asp?id=123314235>.
- [13] DARPA, "Environmental Assessment for Hypersonic Technology Vehicle 2 Flight Tests," April 2009. [Online]. Available: <http://www.dtic.mil/cgi-bin/GetTRDoc?AD=ADA544343>.
- [14] U.S. Army, "Army successfully launches Advanced Hypersonic Weapon demonstrator," 23 November 2011. [Online]. Available: http://www.army.mil/article/69855/Army_successfully_launches_Advanced_Hypersonic_Weapon___/.
- [15] T. R. Jorris, "Hypersonic Vehicles," in *AIAA Speaker's Dinner*, Lancaster, CA, 2012.
- [16] DARPA, "Falcon HTV-2 Launch Tests Hypersonic Vehicle Flight Capabilities," 23 April 2010. [Online]. Available: <http://www.darpa.mil/WorkArea/DownloadAsset.aspx?id=2147484133>.
- [17] DARPA Public Affairs, "DARPA Concludes Review of Falcon HTV-2 Flight Anomaly," 16 November 2010. [Online]. Available: <http://www.darpa.mil/WorkArea/DownloadAsset.aspx?id=2147484134>.
- [18] DARPA, "Engineering Review Board Concludes Review of HTV-2 Second Test Flight," 20 April 2012. [Online]. Available: <http://www.darpa.mil/NewsEvents/Releases/2012/04/20.aspx>.
- [19] J. J. Downey, R. W. Carr, K. I. Bull and T. R. Jorris, "Design of Experiments Using Response Surface Methods to Optimized Simulated Reentry Trajectories," in *28th Aerodynamic Measurement Technology, Ground Testing, and Flight Testing Conference*, New Orleans, Louisiana, 2012.
- [20] T. R. Jorris, "Common Aero Vehicle Autonomous Reentry Trajectory Optimization Satisfying Waypoint and No-Fly Zone Constraints," in *Air Force Institute of Technology*,

Wright-Patterson AFB, OH, 2007.

- [21] J. Foust, "Air launch, big and small," *The Space Review*, 30 June 2014. [Online]. Available: <http://www.thespacereview.com/article/2543/1>.
- [22] R. W. Carr, T. R. Jorris and Jacob J. Downey, "Trajectory Analysis Program for Determining Range Safety Considerations using Multi-Phase Pseudospectral Optimization," in *28th Aerodynamic Measurement Technology, Ground Testing, and Flight Testing Conference*, New Orleans, Louisiana, 25-28 June 2012.
- [23] B. M. Hellman, "Comparison of Return to Launch Site Options for a Reusable Booster Stage," Georgia Institute of Technology, August 2005.
- [24] R. W. Carr, T. R. Jorris and A. V. Rao, "Propagation of Uncertainty in Optimal Trajectory Generation," in *11th Annual AIAA Southern California Aerospace Systems and Technology Conference*, Santa Ana, CA, 3 May 2014.
- [25] S. N. Corporation, "Statement from Sierra Nevada Corporation Regarding Dream Chaser Free-Flight Test," Sierra Nevada News & Press Releases, 26 October 2013. [Online]. Available: http://www.sncorp.com/press_more_info.php?id=569.
- [26] NASA, "Boeing Tests Parachute System for CST-100 Spacecraft," 4 May 2012. [Online]. Available: <http://www.nasa.gov/exploration/commercial/crew/boeingdroptest.html>.
- [27] Space Exploration Technology Corp., "Dragon Overview," May 2012. [Online]. Available: <http://www.spacex.com/dragon.php>.
- [28] U.S. Air Force, "Air Force space vehicle comes in for a landing," 18 June 2012. [Online]. Available: <http://www.af.mil/news/story.asp?id=123306243>.
- [29] NASA, "NASA Range Safety Annual Report," 2011. [Online]. Available: http://kscsma.ksc.nasa.gov/Range_Safety/Annual_Report/2011/PDFDocuments/V_Emerging_Technology.pdf.
- [30] DARPA, "Broad Agency Announcement, Tactical Boost Glide," DARPA-BAA-14-24, 25 March 2014.
- [31] Systems and Sierra Nevada Corporation's Space Systems, "Sierra Nevada Corporation's Dream Chaser Space System Passes Preliminary Design Review," 6 June

2012. [Online]. Available: http://sncspace.com/press_more_info.php?id=335.

- [32] Army Advanced Hypersonic Weapon Flight Test - <http://www.army.mil/article/69855/>

- [33] NASA Tracking and Data Relay Satellites (TDRS) - <https://www.nasa.gov/content/tracking-and-data-relay-satellite-tdrs/> and personal communication with TDRS program personnel.

- [34] Inmarsat - <http://www.inmarsat.com/global-xpress-us-government/>

- [35] Iridium Satellite network - <https://gigaom.com/2012/08/27/how-iridium-took-a-chance-on-spacex-and-won/>

- [36] ORBCOMM - <http://www.orbcomm.com/networks/satellite>

- [37] ViaSat - <https://www.viasat.com/broadband-satellite-networks/high-capacity-satellite-system>

- [38] Rockwell Collins Tactical Targeting Network Technology (TTNT) - <http://rockwellcollins.com/~media/Files/Unsecure/Products/Product%20Brochures/Communication%20and%20Networks/Networks/Tactical%20Targeting%20Network%20Technology/TTNT%20brochure.aspx>



412th Test Wing



412TW

War-Winning Capabilities ... On Time, On Cost



Current Hypersonic Flight Test Instrumentation Challenges

June 2015

U.S. AIR FORCE



John Spravka
Deputy Director, Hypersonic CTF
Edwards AFB, CA
John.spravka@us.af.mil

Distribution: A Approved for public release; distribution is unlimited 412TW-PA-15264

Integrity - Service - Excellence



Overview



412TW

- **Previous Data Collection Systems**
- **Future Program Requirements**
- **Future Data Collection Systems**




Hypersonic CTF Lineage



44TH



X-15



X-20

Dynasoar




X-24A



X-24B

SPACE SHUTTLE



X-24C



X-34

X-30 NASP



X-40A



X-33



X-38



X-37B

X-37A



X-43A



X-51



Manned Spacecraft Office (1959-1969)

- X-15, X-20 Dynasoar

Research Projects Branch (1970-1974)

- X-24A, X-24B Lifting Bodies

Office of Advanced Manned Vehicles (1975-1986)

- Space Shuttle, X-24C, BGV

Research Projects Office (1987-1995)

- X-30 National AeroSpace Plane

Access to Space Office – (1996 – 2003)

- X-33, X-34, X-38, X-40A

Hypersonic Flight Test Team – (2004 – 2007)

- X-43, X-37A

Hypersonic Combined Test Force – (2008 – present)

- X-37B, X-51A, HTV-2, Dream Chaser



Hypersonic CTF Programs



412TW




X-51A
AFRL/RQ, Boeing, Pratt-Whitney
High Speed Strike Weapon
AFRL/RW



**HTV-2, Lockheed-Martin
Integrated Hypersonics** } **DARPA**





Dream Chaser: NASA Commercial Crew Dev
Sierra Nevada Corp, Dryden



X-37B – Orbital Test Vehicle
AF/RCO, Boeing



X-51A Scramjet Engine Demo







X-51A: Pt Mugu Sea Test Range



412TW



Ranges: Pt. Mugu, Vandenberg
Launch point: B-52, 50 kft
Max Alt*: 71 kft MSL
Range: 310 nmi
Sponsor: AFRL (Wright-Patt)



HTV-2

Hypersonic Technology Vehicle



412TH







HTV-2 (Integrated Hypersonics)



•Launch - Vandenberg



•Mid - Avoids Hawaii



•Terminal - Kwajalein



Ranges/Launch:	Vandenberg
Terminal:	Kwajalein
Altitude at coast:	450 kft MSL
Range:	4000+ nmi
Sponsor:	DARPA



HTV-2

Hypersonic Technology Vehicle



110TH




Falcon HTV-2 Baseline Flight Test Trajectories



Dr. Steven Walker & Dr. Peter Erbland

Mission B

Endo flight time = 1409 sec
Endo range = 3079 nm
Endo cross-range = 1250 nm





Future Program Requirements



412TW





Speed is the new stealth



412TW

Hypersonic missiles

Speed is the new stealth

Hypersonic weapons: Building vehicles that fly at five times the speed of sound is hard, but researchers are trying

Jun 1st 2013 | From the print edition

The
Economist





High Speed Strike Weapon



442TM

<http://www.lockheedmartin.com/us/products/high-speed-strike-weapon--hssw--.html>



DEPARTMENT OF THE AIR FORCE

PRESENTATION TO THE SENATE ARMED SERVICES COMMITTEE
SUBCOMMITTEE ON EMERGING THREATS AND CAPABILITIES

18 April, 2013

U.S. SENATE



“The technologies requiring early flight testing are included in a demonstration effort that will begin later in Fiscal Year 2013 called the **High Speed Strike Weapon** (HSSW).”

“ ... compatibility with Air Force 5th generation platforms to include geometric and weight limits for **internal B-2** Spirit bomber carriage and **external F-35** Lightning II fighter carriage.”

“The flight demonstration will be the first **tactically-relevant** demonstration of **Mach 5.0 plus** airbreathing missile technology.



DARPA HAWC



412TW

Objective: Long range strike vs time critical or heavily defended targets.



Vehicle Performance:

Range: Greater than 300 nm

Altitude: Greater than 60K ft

Data Collection/Transmission requirement:

Range greater than vehicle performance range

DARPA-CG-815



DARPA TBG



412TW

Objective: Air launched tactical boost glide demonstration



Vehicle Performance:

Range: Approximately 500 nm

Data Collection/Transmission requirement:

Range greater than vehicle performance range


DARPA-CG-809



Advanced Hypersonic Weapon



412TW



Sandia's Integrated Military Systems Program - AHW

Flight 1A: Nov. 17, 2011, Sandia's Kauai Test Facility to Kwajalein.

Flew almost 2,500 mi in less than 30 min.

Demonstrated viability of boost-glide approach to long-range atmospheric flight and data collection.

AHW was selected as a Lockheed Martin NOVA award winner.

http://www.army.mil/article/69484/DoD_announces_successful_test_of_Army_Advanced_Hypersonic_Weapon_concept/
http://www.sandia.gov/missions/defense_systems/accomplishments/



DARPA ALASA



412TW

Objective:
Deploy a 100 lb
payload to LEO
For less than \$1M
per mission



Instrumentation requirement:
Range equal to payload deployment
altitude


DARPA-BAA-12-07



DARPA: XS-1



Objective:
Deploy 3K – 5k lb
payload to orbit for
under \$5M per launch



Data Collection/Transmission requirement:
Transceive data over very long range at low
to very high altitudes



Future Data Collection Systems



412TW

Ground Based



Aircraft Based



Space Based






Ground Based



412TW

HALAS - High Altitude LIDAR Atmospheric Sensing

- Measures atmospheric density, temperature, pressure, wind speed/direction, O₂ content
- Ultra-violet laser and scanner; 80km ceiling
- Ground-based, portable; reduced uncertainty
- Replaces weather balloons and chase aircraft





Ground Based



412TW

HALAS - High Altitude LIDAR Atmospheric Sensing

- Predicted air density uncertainty values
- Actuals show balloon equivalence at lower altitudes but match predictions at higher altitudes

Altitude (kft)	Balloon Uncertainty	HALAS Uncertainty
20	0.47%	0.023%
30	0.49%	0.021%
40	0.63%	0.022%
50	0.71%	0.027%
60	1.01%	0.036%
70	1.30%	0.050%
80	1.87%	0.069%
90	2.86%	0.092%
100	4.57%	0.120%



Aircraft Based



412TW

- Example trajectories requiring TM & FTS coverage





Aircraft Based



412TW

High Altitude UAVs

- Provide sufficient coverage
- Can support multiple data transmission/collection systems





Aircraft Based



412TW

High Altitude UAVs

- Reduce test costs
- Long duration time-on-station & positioned closer to flight path
- Quantitative
 - Remote sensing/imaging
 - Telemetry data collection/relay
 - TSPI/flight safety
 - Atmospheric characterization
- Critical data for mishap/anomaly investigation; quicker return to flight
- Enable high-G terminal maneuver OT&E over open ocean not allowed at current ranges





Aircraft Based



412TW

Data Links

- Link 16 could get around 128kpbs
- Link 16 block 2 should double that (2016-ish)
- TTNT claims it is good up to Mach 8 (Mach 12 with a strong signal) with 10Mbps for 300nm
- TTNT seems to be the best candidate



Space Based



412TW

- **TDRS - NASA Tracking and Data Relay Satellites**
- **Inmarsat**
- **Iridium**
- **ORBCOMM**
- **ViaSat**



Space Based



- **Advantages**
 - Extended range coverage
 - Cost is competitive
 - Open for business
- **Limitations**
 - Data rates/bandwidth not currently sufficient
 - Transcievers require space, power and cooling
 - Vehicle tracking not easy



Questions?



412TW

John J. Spravka
Deputy Director, Hypersonic CTF
Edwards AFB, CA
John.spravka@us.af.mil

